



UNIT SIZE	INLET SIZES	WIDTH	HEIGHT
	D	W	H
4	3 7/8 (98)	12 (305)	8 (203)
5	4 7/8 (124)		
6	5 7/8 (149)		
7	6 7/8 (175)		10 (254)
8	7 7/8 (200)	14 (356)	12 1/2 (318)
9	8 7/8 (225)		
10	9 7/8 (251)		
12	11 7/8 (302)		15 (381)
14	13 7/8 (352)	20 (508)	17 1/2 (445)
16	15 7/8 (403)	24 (610)	18 (457)

STANDARD CONSTRUCTION:

- 1" (25mm) THICK INTERNAL FIBERGLASS INSULATION WHICH MEETS REQUIREMENTS OF NFPA 90A AND UL181.
- 22 GAUGE GALVANIZED STEEL HOUSING. MECHANICALLY SEALED, LEAK RESISTANT CONSTRUCTION.
- RECTANGULAR INLET & DISCHARGE OPENING WITH SLIP AND DRIVE CLEAT DUCT CONNECTION.
- MULTI-POINT, CENTER AVERAGING AIRFLOW SENSOR.
- 1/2" (13mm) GALVANIZED DAMPER SHAFT WITH POSITION INDICATOR.
- RIGHT HAND UNIT SHOWN (CRH), LEFT HAND AVAILABLE.

CONTROLS OPTIONS:

- FIELD MOUNTED CONTROLS, SUPPLIED BY OTHERS (FLD)
- FACTORY MOUNTED DIGITAL CONTROLS, SUPPLIED BY OTHERS (FAC)
- FACTORY MOUNTED DIGITAL CONTROLS, SUPPLIED BY PRICE (EHPD)

UNIT OPTIONS:

- NEMA1 CONTROLS ENCLOSURE (PS)
- DISCONNECT SWITCH (DSW)
- HANGER BRACKETS (HB)
- BOTTOM REMOVABLE SENSOR (RS)
- BRASS AIRFLOW SENSOR GAUGE TAPS (GT)

LINER OPTIONS:

- FIBER FREE FOAM 1" (25mm) (FF1)
- SOLID METAL WITH FG1 (SM1)
- CLEANROOM ANGLES WITH FB1 (CRAF1)
- PERFORATED METAL WITH FB1 (AFPM1)
- CLEANROOM ANGLES (CA) WITH FG1 OR FF1



ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		PRICE [®]	
ENGINEER:		APPROVED BY: GH	SDE SINGLE DUCT EXHAUST VARIABLE VOLUME W/ ATTENUATOR
CUSTOMER:		DRAWING NO: 276532	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 2024-02-08	