



IMPERIAL UNITS (inches)			
UNIT SIZE	W	H	L
30	24 1/2	12 1/4	43 1/2

SI UNITS (mm)			
UNIT SIZE	W	H	L
30	622	311	1105

ECM MOTOR FLA					
SIZE	MOTOR H.P	115V	208V	240V	277V
30	1/2	7.7	4.3	4.3	4.1

**STANDARD CONSTRUCTION:**

- INTERNAL INSULATION - FIBERGLASS 1/2" (13mm) THICK, MINIMUM 1.5 LB/CU.FT DENSITY WHICH MEETS REQUIREMENTS OF NFPA 90A & UL181.
- ZINC COATED 20 GAUGE STEEL HOUSING.
- ECM ELECTRICAL MOTOR, 1 PHASE, 60 CYCLE, SPEED CONTROLLER INCLUDED.
- MERV 8 PRE FILTER & HEPA FILTER.
- LEFT HAND CONTROLS CONFIGURATION SHOWN ABOVE. RIGHT HAND ALSO AVAILABLE.
- BOTTOM BLOWER ACCESS PANEL.
- INLET AND DISCHARGE DESIGNED FOR SLIP & DRIVE CLEAT DUCT CONNECTIONS.
- LEFT HAND CONFIGURATION SHOWN ABOVE. RIGHT HAND UNIT MIRROR OF LEFT HAND
- HEPA RATING OF 99.97% EFFICIENCY
- MERV8/MERV13 WITH CARDBOARD FRAME
- ASSEMBLY LISTED UNDER UL507/CSA 22.2 No. 113

**OPTIONS:**

- DISCONNECT SWITCH (DSW)
- HANGER BRACKETS (HB), SHIPPED LOOSE
- 2" MERV 13 FILTER (IN LIEU OF HEPA AND MERV8 PREFILTER)
- FRESH AIR INLET (FAI)

**LINERS:**

- FF50



ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		<b>PRICE</b>
ENGINEER:	<i>BS</i>	
CUSTOMER:	<b>272988</b>	<b>OAP OVERHEAD AIR PURIFIER FILTRATION UNIT SIZE 30</b>
SUBMITTAL DATE:	11/06/2025	
SPEC. SYMBOL:		